

339 Black Foam

PROFESSIONAL GRADE

Part Number:
33924



- Excellent adhesions on most substrates
- High thermal and acoustical insulation
- For automotive and exterior use
- Excellent mounting capabilities
- Reduces auto noise pollution
- No discoloration due to UV radiation
- Very good filling capabilities
- Very precise application due to foam gun system
- Fish and plant safe

THE IDEAL SEALANT/ADHESIVE FOR:

- Sealing gaps in RV and automotive undercarriage
- Crack and repair holes in trees
- Fill and seal gaps and cracks in pond and waterfall design
- Sealing gaps and penetrations in building envelope



Foam Gun w/ Threaded Tip
M0098



Foam Gun 22"
M0123

Visit Our Website for Other
BOSS[®] MADE TO WORK Products
www.bossproducts.com

Call The **BOSS[®]** 800-928-BOSS

Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

339 Black Foam

PROFESSIONAL GRADE

TYPICAL PROPERTIES

Skin-over Time	ca. 8 minutes (68°F & 65% R.H.)
Tack Free.....	Dustfree after 20-25 min. at 68°F
Cure Time (1/8" bead)	1 hour
Tensile Strength	4.35 psi
Shear Strength.....	8.7 psi
Yield/24 oz. Can	9-10 gallons of cured foam
Theoretical Yield - 24 oz. 1/4" bead	4005 ft.
Elastic Recovery (ISO 1856).....	Until 92% (75% compressed)
Acoustic Rating (EN ISO 717-1).....	$R_{ST,W}(c;c_{tr}) = 60 \text{ dB } (-1;-4)$
Service Temperature	-40°F to 194°F
Application Temperature	41°F to 95°F

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

- Ground shipments only. Cannot ship by air.
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

DANGER!

EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.

Call The **BOSS[®]** 800-928-BOSS

Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

www.bossproducts.com

