

Safety Data Sheet

BOSS® 333 Gap Fill Foam Straw Grade

Section 1. Identification

Product Identifier

BOSS® 333 Gap Fill Foam Straw Grade

Synonyms

BOSS® 333 g Foam Straw Grade; 33320; 33316; 02455BR10; 01551BR10

Manufacturer Stock

02455BR10; 01551BR10

Numbers

Recommended use

Refer to Technical Information

Uses advised against

Refer to Technical Information

Manufacturer Contact

Address

Soudal Accumetric

350 Ring Road

Elizabethtown, KY, 42701

USA

Phone

Emergency Phone

Fax

(270) 769-3385

(800) 424-9300

(270) 765-2412

CHEMTREC

Section 2. Hazards Identification

Classification ACUTE TOXICITY - INHALATION - Category 4

CARCINOGENICITY - Category 2

EYE DAMAGE/IRRITATION - Category 2A FLAMMABLE AEROSOLS - Category 1

HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -

Category 4

SENSITIZATION - RESPIRATORY - Category 1

SENSITIZATION - SKIN - Category 1

SKIN CORROSION/IRRITATION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3
TOXIC TO REPRODUCTION - EFFECTS ON OR VIA LACTATION

Signal Word

Pictogram

Danger



Hazard Statements

Causes serious eye irritation

Causes skin irritation

Extremely flammable aerosol

Harmful if inhaled

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure.

May cause harm to breast-fed children

May cause long lasting harmful effects to aquatic life

May cause respiratory irritation. Suspected of causing cancer.

Precautionary Statements

Response

Get medical advice/attention if you feel unwell.

If experiencing respiratory symptoms: Call a poison center/doctor.

If exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If inhaled: If breathing is difficult, remove person to fresh air and keep

comfortable for breathing.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If medical advice is needed, have product container or label at hand.

If on skin: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Prevention

Avoid contact during pregnancy/while nursing.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the workplace.

Do not breathe spray.

Do not eat, drink or smoke when using this product.

Do not handle until all safety precautions have been read and understood.

Do not spray on an open flame or other ignition source.

In case of inadequate ventilation wear respiratory protection.

Keep away from heat.

Obtain special instructions before use.

Pressurized container: Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.

Wear eye protection/face protection.

Wear protective gloves.

Wear protective gloves/protective clothing.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/

international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Additional information Contains isocyanates. May produce an allergic reaction.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
74-98-6	Propane	5% - Max
9016-87-9	Polymeric diphenylmethane diisocyanate	40% - 50%
115-10-6	Dimethyl ether	1% - 10%
13674-84-5	2-Propanol, 1-chloro-, phosphate (3:1)	1% - 10%
75-28-5	Isobutane	1% - 10%
85535-85-9	alkanes, C14-17, chloro	1% - 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

General information Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

After inhalation Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for

transportation.

After skin contact If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. Then consult a

doctor.

After swallowing Call for a doctor immediately.

Most important symptoms

No further relevant information available.

and effects, both acute and

delayed

Indication of any immediate No further relevant information available.

medical attention and special treatment needed

Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Foam, CO2, sand, extinguishing powder. Do not use water.

Unsuitable Extinguishing

Media

Special hazards arising from the substance or

mixture

In case of fire, the following can be released: Nitrogen oxides (NOx)

Carbon monoxide (CO) Hydrogen cyanide (HCN)

Advice for firefighters Protective equipment: Mouth respiratory protective device.

Additional information: Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Water with full jet

Section 6. Accidental Release Measures

Personal precautions,

protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away.

Environmental precautions Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Methods and material for

containment and cleaning

up

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Do not flush with water or aqueous cleansing agents

Reference to other

sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7. Handling and Storage

No Data Available

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Propane	1000 ppm TWA	1000 ppm PEL	N/A

Polymeric diphenylmethane diisocyanate	0.005 ppm	0.02 mg/m≈	N/A
Dimethyl ether	N/A	400 ppm	N/A
2-Propanol, 1-chloro-, phosphate (3:1)	N/A	N/A	N/A
Isobutane	1000 ppm	N/A	1000 ppm
alkanes, C14-17, chloro	N/A	N/A	N/A

Personal Protective

Equipment

Gloves

Occupational Exposure

Controls

Use only in well ventilated areas.

Eye Protection Use proper protection - safety glasses as a minimum.

Skin Protection Chemically resistant gloves and suitable protective clothing.

Respiratory Protection In case of insufficient ventilation, use respiratory protection with filter Type A.

Section 9. Physical and Chemical Properties

Physical State	Aerosol	
Color	Refer to	
	product label	
Odor	Characteristic	
Odor Threshold	N/A	
Solubility	Insoluble in	
	water	
Partition coefficient Water/n-octanol	N/A	
VOC%	25% (by wt)	
	235 g/L	
Viscosity	N/A	
Specific Gravity	N/A	
Density lbs/Gal	N/A	
Pounds per Cubic Foot	N/A	
Flash Point	-21C	
FP Method	N/A	
рН	N/A	
Melting Point	Undetermined	
Boiling Point	Undetermined	
Boiling Range	N/A	
LEL	3	
UEL	18.6	
Evaporation Rate	N/A	
Flammability	N/A	
Decomposition Temperature	N/A	
Auto-ignition Temperature	N/A	
Vapor Pressure	N/A	
Vapor Density	N/A	

Section 10. Stability and Reactivity

Materials to Avoid

Keep away from heat sources, ignition sources, acids, and bases.

Conditions to Avoid -

Reactivity

Products

Unstable on exposure to heat.

Hazardous Decomposition On burning: release of toxic and corrosive gases/vapors: hydrogen chloride,

carbon monoxide and carbon dioxide.

On heating: release of toxic /combustible gases/vapors (hydrogen cyanide).

May polmerize on exposure to temperature rise.

May polymerize with a lot of compounds, ex; (Strong) bases and amines.

Reacts violently with (some) acids/bases.

Section 11. Toxicological Information

Primary irritant effect on the skin: Irritant to skin and mucous membranes.

on the eye: Irritating effect.

Sensitization Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological

information

The product shows the following dangers according to the calculation method of

the General EU Classification Guidelines for Preparations as issued in the

latest version:

Harmful Irritant

CMR effects (carcinogenity, Carc. 2, Lact.

mutagenicity and toxicity for

reproduction)

Section 12. Ecological Information

No further relevant information available. Aquatic toxicity

Persistance and

degradibilty

information

No further relevant information available.

Bioaccumulative potential No further relevant information available.

No further relevant information available. Mobility in soil

Additional ecological

Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water,

water course or sewage system.

Results of PBT and vPvB

assessment

PBT: Not applicable. vPvB: Not applicable. Other adverse effects

No further relevant information available.

Section 13. Disposal

Waste Disposal Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

Uncleaned Packaging Recommendation

Disposal must be made according to official regulations.

Section 14. Transport Information

UN Number 1950

UN Proper Shipping Name AEROSOLS, flammable

DOT Classification N/A 2.1 Packing Group

DOT Road Shipment

Hazard Class: 2.1

Information

Identification Number: UN1950

Packing Group: -

Proper Shipping Name: AEROSOLS, flammable, n.o.s.

Label: 2.1

Air Shipment (IATA)

ICAO/IATA Class: 2.1 UN/ID Number: 1950

Label: 2.1

Packaging Group: -

Proper Shipping Name: AEROSOLS, flammable, n.o.s.

Ocean Shipment (IMDG)

Hazard Class: 2.1 UN Number: 1950

Label: 2.1

Packing Group: -EMS Number: 2-13 Marine Pollutant: No

Section 15. Regulatory Information

Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects. For more information,

go to www.P65Warnings.ca.gov

Section 16. Other Information

Revision Date 6/1/2018

Disclaimer The data contained herein is based upon information that Soudal Accumetric

believes to be reliable. Users of this product have the responsibility to determine

that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.