

BOSS[®] 385 Tub & Tile Plumbers 100% RTV Silicone

TYPICAL PROPERTIES

Type.....One part, ready-to-use silicone rubber
Special PropertiesMildew and moisture resistant
Benefits Long-life reliability,
permanently flexible, good appearance
Primary Use..... Sealing nonporous surfaces around
ceramic tile, showers, tubs, sinks and plumbing fixtures

As supplied

Color..... Clear, white, translucent white, almond
Flow, sag or slump NIL
Tack-Free Time..... 15-20 minutes
Cure Time (1/8" thickness)24 hours
Service Temperature.....-40°F to 400°F
Application Temperature-35°F to 140°F

*Information on this data sheet is subject to change without notice
and should not be used for writing specifications.

For additional information on specific applications, contact Soudal Accumetric



DESCRIPTION

BOSS[®] 385 Tub & Tile Plumbers 100% RTV Silicone is a one-part, fungicidal, silicone rubber sealant designed to seal nonporous surfaces around ceramic tile, showers, tubs, sinks and plumbing fixtures where conditions of high humidity and temperature extremes exist.

BOSS[®] 385 Tub & Tile Plumbers 100% RTV Silicone:

- Resists mildew even in prolonged hot and humid environments
- Resists staining, spotting and color change
- Remains flexible – will not shrink, crack, crumble or dry out
- Stays bright and clean
- Is ready-to-use as supplied
- Resists moisture, hot cooking oils and free steam
- Adheres to many nonporous surfaces such as porcelain, painted areas and glass without the use of a primer

USES

BOSS[®] 385 Tub & Tile Plumbers 100% RTV Silicone is mildew resistant. It is used for such nonporous surface applications as:

- **Sealing around shower-tub enclosures, tubs, sinks and around urinals**
- **Sealing around bathroom fixtures**
- **Waterproofing rimless sinks**
- **Ceramic tile grouting**

HOW TO USE

BOSS® 385 Tub & Tile Plumbers 100% RTV Silicone must always be applied to sound, clean, dry, frost-free surfaces.

Tooling is recommended and if possible, should be completed in one continuous stroke. Tool joints within 10 minutes of application. Remove masking tape before a surface skin has formed.

Cleaning the joint surface on both new and old jobs

Bonding surfaces on both new and remedial jobs must be clean, dry and free of dirt, dust and soap film.

Use masking tape where bead lines of exact shapes are required

Use masking tape before applying sealant and remove immediately after a bead is completed and before a skin forms (7 to 15 minutes).

Applying the sealant

BOSS® 385 Tub & Tile Plumbers 100% RTV Silicone can be applied directly from the caulking cartridge with either an air operated or hand operated cartridge gun. Do not break the cartridge seal until just before using.

After applying the sealant and after a skin has formed, do not disturb the joint for 48 hours. A previously opened cartridge may be reused by removing the cured plug of sealant from the tip.

LIMITATIONS

BOSS® 385 Tub & Tile Plumbers 100% RTV Silicone is not recommended for continuous water immersion, nor for floor joints where abrasion and physical abuse are encountered. It should not be applied to:

- Porous surfaces such as masonry
- Building materials that bleed oils or solvents, such as impregnated wood and certain partially vulcanized rubber gaskets, tapes or adhesives
- Totally confined spaces, because the sealant needs atmospheric moisture to cure

COLORS

BOSS® 385 Tub & Tile Plumbers 100% RTV Silicone is available in clear, white, translucent white and almond.

SPECIFICATIONS

BOSS® 385 meets Federal Specifications TT-S-001543A, TT-S-00230C and ASTM C920-86

PACKAGING

BOSS® 385 Tub & Tile Plumbers 100% RTV Silicone is available in standard caulking cartridges and 4.5 gallon pails. Other sizes available upon request.

CLEAN UP

Uncured sealant can be easily removed using a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **BOSS® 385** Tub & Tile Plumbers 100% RTV Silicone has a shelf life of 12 months from date of shipment. In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE, AND THROAT. Avoid eye and skin contact. Use with adequate ventilation. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. Sealant releases acetic acid (vinegar-like odor) during cure. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

SHIPPING LIMITATIONS

None.
Reactive VOC 29 g/l (<3% wt)

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Soudal Accumetric's control, we can accept no liability for the results obtained. Soudal Accumetric's sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Soudal Accumetric will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

MADE IN U.S.A.

BOSS® PRODUCTS

Soudal Accumetric
350 Ring Road
Elizabethtown,
Kentucky 42701 USA
800-928-BOSS(2677)
TEL (270)769-3385
FAX (270)765-2412
Outside U.S.
TEL +1(270)769-3385
FAX +1(270)765-2412

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662)634-3060
FAX (662)634-3066

www.bossproducts.com