

**BOSS®**  
**PRODUCTS**



# 185 Multi-Seal®

**QUICK GRAB  
INDUSTRIAL • CONSTRUCTION**

**Colors:**  
**Cartridge**  
White - 18501



- Immediate high grab strength to most substrates
- Plastic cartridge
- Formulated with USP™ technology
- Paintable with most latex paints\*
- Can be applied on wet surfaces
- UV Resistant and color stability
- VOC compliant

\*Test small area for compatibility before painting

#### THE IDEAL SEALANT/ADHESIVE FOR:

- Aluminum
- Steel
- Glass
- Wood
- Brick
- Mirrors
- Concrete
- Many Plastics

Visit Our Website for Other  
**BOSS® MADE TO WORK** Products  
[www.bossproducts.com](http://www.bossproducts.com)

Call The **BOSS®** 800-928-BOSS

**Soudal Accumetric**

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

# 185 Multi-Seal<sup>®</sup>

## QUICK GRAB INDUSTRIAL • CONSTRUCTION

### TYPICAL PROPERTIES

#### Uncured

Appearance .....	Smooth
Color .....	White
Specific Gravity .....	1.6
Sag/Slump .....	Nil
Extrusion Rate .....	250 g/min.
Tack Free Time at 75°F (24°C) and 50% RH .....	20 min.

#### Cured-Physical

Durometer, Shore A Hardness .....	48 points
Ultimate Tensile Strength .....	420 psi
Elongation .....	480%
Modulus .....	250 psi
Solid .....	98%
Service Temperature .....	-40°F to 200°F
Application Temperature .....	-35°F to 140°F

Primers may be required for certain substrates  
Information on this data sheet is subject to change without notice and should not be used for writing specifications.  
For additional information on specific applications, contact Soudal Accumetric.

### LIMITATIONS

- Do not use for structural glazing
- Do not use as a window glazing sealant
- Not recommended for use on PE, PP or PTFE (Teflon<sup>®</sup>) due to poor adhesion to these substrates

### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The **BOSS<sup>®</sup>** 800-928-BOSS  
Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412  
[www.bossproducts.com](http://www.bossproducts.com)

