

370 HVAC Silicone

HEATING • VENTILATION • AIR CONDITIONING

Colors:

Cartridge

Clear - 37000
White - 37001
Black - 37002
Aluminum - 37003

Pressure Can:

Clear - 37008
White - 37081
Aluminum - 37083



- Plastic cartridge or Pressure can
- One year shelf life
- Weatherproof Seal
- Fast Cure
- Meets TT-S-001543A, TT-S-00230C, and ASTM C-920-86
- VOC compliant

THE IDEAL SEALANT/ADHESIVE FOR:

- General Heating
- Ventilation
- Air Conditioning
- Ducts
- Fixtures
- Piping
- Wood
- Metal
- Glass
- Electrical Connections
- Silicone Resins
- Vulcanized Silicone Rubber
- Ceramics
- Plastic Surfaces
- And more...

Visit Our Website for Other
BOSS[®] MADE TO WORK Products
www.bossproducts.com

BOSS[®] 150 Multi-Seal[®] Industrial,
Cold Storage, Refrigeration,
Construction Sealant

BOSS[®] 350 Fire Retardant Duct Sealant

BOSS[®] 376 Hi-Temp Red RTV Silicone

Call The **BOSS[®]** 800-928-BOSS

Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412



370 HVAC Silicone

HEATING • VENTILATION • AIR CONDITIONING

TYPICAL PROPERTIES

Uncured

Colors (cartridge).....	clear, white, black, aluminum
Colors (pressure can)	clear, white, aluminum
Custom colors upon request	
Slump	NIL
Tack-Free Time.....	(77°F & 50% RH)
10 - 20 minutes Extrusion Rate	350 gr/min.

Cured

(7 days at 77°F+3°F and 50% and +5% TH)

Elongation	500
Durometer, Shore A	18
Tensile Strength	300 psi
Movement Capability	±25%
Service Temperature	-40°F to 400°F
Application Temperature	35°F to 140°F

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

- Do not use for structural glazing
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The **BOSS[®]** 800-928-BOSS

Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

www.bossproducts.com

