

# BOSS<sup>®</sup> PRODUCTS



# 400 COLORS

## SIDING • WINDOW & METAL ROOF SEALANT

**Colors:**  
Various Colors -  
Part Number  
Beginning With  
03889+



- 50% Movement
- Plastic cartridge
- One year shelf life
- Available in 400+ Colors that match all the major Siding, Window, Roofing and Metal Roofing colors.
- Will not shrink
- VOC compliant in all 50 states
- Minimal Odor
- 4 inch nozzle for hard to reach areas
- Interior & Exterior Applications
- Bonds to Kynar<sup>®</sup> 500

Kynar<sup>®</sup> 500 is a trademark of Arkema Inc.

### THE IDEAL SEALANT/ADHESIVE FOR:

- Metal Roofing
- Siding
- Windows
- Concrete
- Brick
- Gutters
- Wood
- Glass
- Aluminum
- And more...

Visit Our Website for Other  
**BOSS<sup>®</sup> MADE TO WORK** Products  
[www.bossproducts.com](http://www.bossproducts.com)

- BOSS<sup>®</sup> 535** Multi-Purpose Polyurethane Sealant
- BOSS<sup>®</sup> 380** Contractor's RTV Silicone Adhesive/Sealant
- BOSS<sup>®</sup> 125** Multi-Seal<sup>®</sup> Roofing, Gutter, Concrete, Construction Sealant

Call The **BOSS<sup>®</sup>** 800-928-BOSS  
**Soudal Accumetric**

350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412



# 400 COLORS

## SIDING • WINDOW & METAL ROOF SEALANT

### TYPICAL PROPERTIES

#### Uncured

Specific Gravity – White & Most colors .....	1.18
Clear .....	1.03
Sag/Slump.....	NIL
Tack-Free Time.....	20 min.
Cure Time at 75°F (24°C) and 50% RH (3/8" thickness).....	24 hours
Extrusion Rate .....	250 g/min.

#### Cured – Physical

Elongation .....	550%
Durometer Hardness, Shore A, points .....	25
Tensile Strength, psi .....	240
VOC – White & Colors .....	40 grams/liter
Clear .....	38 grams/liter
Service Temperature.....	-40°F to 325°F
Application Temperature .....	-35°F to 140°F

Primers may be required for certain substrates.

Information on this data sheet is subject to change without notice and should not be used for writing specifications.  
For additional information on specific applications, contact Soudal Accumetric.

### LIMITATIONS

- Do not use for structural glazing
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The **BOSS<sup>®</sup>** 800-928-BOSS  
Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412  
[www.bossproducts.com](http://www.bossproducts.com)

