

BOSS®
PRODUCTS



814 FireStop

INTUMESCENT LATEX

Part Numbers:

Cartridge 10.1 Oz. - 81410
Sausage 20 Oz. - 81420
Cartridge 29 Oz. - 81429
Pail 4.5 Gal. - 81450



- Available In
10.1 oz cartridge,
20 oz sausage,
29 oz cartridge, and
4.5 gal. pail
 - Interior/exterior use
 - Water clean up
 - Paintable (after inspection)
- Listed to UL 1479 (ASTM E-814), meets IRC, UBC, CABO, BOCA (NBC) IBC

Call The **BOSS®** 800-928-BOSS
350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

814 FireStop

INTUMESCENT LATEX

TYPICAL PROPERTIES

Color	Red
Specific Gravity	1.42
Consistency (ASTM C639-5)	Non Slump
Skin Forming Time	15 minutes @ 75°F
Ultimate Elongation	600%
Joint Movement	±12.5%
Curing Time	Full cure in 14 to 20 days
Freeze/Thaw	Excellent
Tested To	ASTM E-814 (UL 1479)
*STC Value	53
Service Temperature	-20°F to 185°F
Application Temperature	40°F to 110°F

* Application per ASTM C919

*Information on this data sheet is subject to change without notice and should not be used for writing specifications.
For additional information on specific applications, contact Soudal.

CAUTION

- Keep from freezing
- Do not take internally
- Keep out of reach of children

For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The **BOSS[®]** 800-928-BOSS
350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412
www.bossproducts.com

