

# BOSS<sup>®</sup> PRODUCTS



# 816+ Firestop

## INTUMESCENT FIRESTOP SEALANT

Replaces BOSS<sup>®</sup> 816.

Now with more UL systems and certifications  
from FBC<sup>™</sup> & Clean Air Gold.

**Part Numbers:**

10.1 Oz. - 81612  
Sausage 20 Oz. - 81621  
Pail 5 Gal. - 81650



- More UL systems
- Adheres to plastic and pex pipe
- Excellent adhesion, mildew resistant
- Intumesces rapidly to close off voids caused by heat or fire
- Remains flexible
- VOC Compliant
- Freeze thaw stable
- Safe to use and handle
- Water based and paintable (after inspection)
- 12 month shelf life



Visit Our Website for Other  
**BOSS<sup>®</sup> MADE TO WORK** Products  
[www.bossproducts.com](http://www.bossproducts.com)

- BOSS<sup>®</sup> 350** Fire Retardant Duct Sealant
- BOSS<sup>®</sup> 814** Intumescent Latex Firestop Sealant
- BOSS<sup>®</sup> 136** Draftstop Sealant
- BOSS<sup>®</sup> 812** Fireblock Straw Grade Foam
- BOSS<sup>®</sup> 812** Fireblock Gun Foam
- BOSS<sup>®</sup> 812** Fireblock Genius Gun



Call The **BOSS<sup>®</sup>** 800-928-BOSS  
350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

# 816+ Firestop

## INTUMESCENT FIRESTOP SEALANT

### TYPICAL PROPERTIES

Color.....	Red
pH.....	7 to 8
Volatile Organic Content.....	5 g/l
Skin Forming Time .....	30 minutes @ 77°F
Density.....	10.75 lbs./gal.
Elastomeric.....	Yes
Curing Time @77°F.....	21 to 28 days
Freeze/Thaw .....	Excellent
STC Rating .....	53
Tested To .....	ASTM E-90
Service Temperature.....	-20°F to 185°F
Application Temperature .....	40°F to 110°F

\*Information on this data sheet is subject to change without notice and should not be used for writing specifications.  
For additional information on specific applications, contact Soudal.

### DANGER!

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN.  
OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT.

Call The **BOSS<sup>®</sup>** 800-928-BOSS

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

[www.bossproducts.com](http://www.bossproducts.com)

