

## Acrylic Latex with Silicone

### TYPICAL PROPERTIES

% Non-Volatile, by weight (colors)	81%
% Non-Volatile, by weight (clear)	61%
% Volume Shrinkage: ASTM C-733-87	28%
Weight per gallon, approximate (colors)	13.5 lb./gal.
Weight per gallon, approximate (clear)	9.1 lb./gal.
pH	8.0
Tack-Free Time: ASTM D-2377-84	<25 min.
Peel Strength - Wood	27.0 pounds-force
Peel Strength - Glass	27.5 pounds-force
Peel Strength - Aluminum	30.0 pounds-force
ASTM C-731-87	16.1 grams/second
VOC	28 g/l
Service Temperature	-20°F to 185°F
Application Temperature	40°F to 110°F

### DESCRIPTION

**BOSS® 363 Sealant Acrylic Latex Caulk with Silicone** is mildew resistant and designed for both interior and exterior use. **BOSS® 363 Sealant Acrylic Latex Caulk with Silicone** forms a tough, flexible resilient bond to all building material surfaces. It has excellent resistance to water, weathering and moisture vapor. **BOSS® 363** cures to produce a flexible seal that is non-yellowing.

### HOW TO USE

**BOSS® 363 Sealant Acrylic Latex Caulk with Silicone** should only be used where moderate joint movement is anticipated. In joints exceeding 1-1/2" in depth use a foam joint filler.

Tooling is recommended and, if possible, should be completed in one continuous stroke.

Tool joints within 10 minutes of application. If masking tape has been used to obtain a cleaner joint, it should be removed before the tack-free skin forms.

**CAUTION:** Do not apply when building material or air temperature is below 40°F. **BOSS® 363 Sealant Acrylic Latex Caulk with Silicone** is not recommended for continuous water immersion or vehicular or foot traffic.

### SPECIFICATIONS

- ASTM C-834-76

### PAINTABILITY

A minimum of 2 hours dry time is required before painting with latex or oil base paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

### CLEAN UP

Excess caulk should be cleaned off tools and nonporous surfaces while it is in the uncured state, using a wet cloth. Cured compounds should be cut away.

Continued...



### APPLICATIONS

- Sealing around window and door frames
- Sealing around baseboards
- Sealing around trim
- Sealing anywhere a weathertight seal is desired
- Sealing corner joints
- Sealing where siding meets trim
- Air seal and weatherization
- MANY MORE...

Scan the QR Code to see the full line of **BOSS® PRO** Products!



## SHIPPING LIMITATIONS

None | Nonreactive VOC 28 g/l (<1.5% wt.)

## CAUTION

DIRECT CONTACT OF UNCURED SEAL-ANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

## STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **BOSS® 363** has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

## TECHNICAL DATA SHEET

### COLORS

- Clear
- White
- Almond
- Grey
- Cedar
- Brown
- Bronze
- Special colors available upon request

### PACKAGING

- Standard caulking cartridges
- 4.5 gallon pails
- 48 gallon drums

**Limited Warranty:** Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



**Soudal Accumetric**

MADE IN U.S.A.

350 Ring Road  
Elizabethtown, KY 42701  
800-928-BOSS(2677)  
270-769-3385  
FAX 270-765-2412  
[www.bossproducts.com](http://www.bossproducts.com)

BOSS is a registered trademark of Soudal