

Dynatex[®]



Manufactured under Patent
No. 10106309

GENIUS GUN REPAIR FOAM

DYNATEX REPAIR FOAM is a top of the line, one-component, moisture curing PU foam. This low pressure formulation makes it ideal for sound and thermal insulation, sealing and filling all types of joints, gaps and cavities.

DYNATEX REPAIR FOAM is ideal for restricting air, sound, dirt and water vapor in a wide variety of applications such as: Inside refrigerated trailers to bond fiberglass liners to prepared spray foam insulation and aluminum posts, grain drying bins, barns, coops, and cut-out buildings, filling joints, and insulating wall panels.



• **Reusable Up to Six Weeks**

• **No Mixing or Calibrating**

• **Ideal for Small Gap Fills**

• **More Cost Effective Per Job Than Canisters**

Dynatex®

GENIUS GUN REPAIR FOAM

MINIMAL EXPANDING POLYURETHANE FOAM

TYPICAL PROPERTIES

Density	1.56 lbs./ft. ³
Thermal Conductivity	0.22 - 0.26 Btu- in/hr-F-ft ²
R Value	3.8-4.8 per inch
Tack Free (1" bead)	8 minutes (68°F & 65% RH)
Fully Cured (1" bead)	12 hours (68°F & 65% RH)
Cuttable (1" bead)	1 hour (68°F & 65% RH)
Tensile Strength	15 psi
Shear Strength	7 psi
Elongation	20%
Yield/24 oz. can	6.6 gallons freely foamed
Theoretical Yield-20 oz. 1/4" bead	2279 ft.
20 oz. 1/2" bead	577 ft.
VOC	175 grams/liter

Service Temperature: -40°F to 200°F

Application Temperature: -35°F to 140°F

**Information on this sheet is subject to change without notice, and should not be used for writing specifications. For additional information, contact Dynatex.

SOUDAL

Dynatex®
STICK TOGETHER.

RepairFoams/053019



350 Ring Road
Elizabethtown, KY 42701, USA
270-769-5557 • 800-999-2937
FAX: 270-769-6418
www.dynatexinc.com