

# **Dynatex®**

## **Copper Gasket Spray/Adhesive/Sealant**

**Dynatex Copper Gasket Spray Adhesive/Sealant** is an aerosol product formulated as an adhesive/sealant which helps dissipate heat and prevents gasket burnout.

Typical applications include cylinder head gaskets, exhaust manifold gaskets, turbo charger flanges, and carburetor gaskets. It contains metallic copper to improve heat transfer and eliminate hot spots. This product is typically used in applications with an operating range of -46 °C to 260 °C (-50°F to 500°F); resists all types of automotive fluids, especially gasoline.



- ***Eliminate hot spots***
- ***Improve heat transfer***
- ***Works in temperatures from -50°F and 500°F***
- ***Remains tacky to allow gasket repositioning***
- ***Resists shop fluids, including gasoline***
- ***Fills surface imperfections***
- ***Prevents gasket burnout***

ITEM # 49583

PART # 145202

DESCRIPTION:: Copper Aerosol Gasket Adhesive 9 Oz. Net  
CASE QTY 12



## Copper Gasket Spray/Adhesive/Sealant

### Properties of Material *Typical Value*

Chemical

Type.....Phenolic

Appearance.....Metallic Copper Film

Odor.....Solvent

Cure.....Air dry

Flash Point.....Aerosol, contents under pressure, consult SDS

NFPA 704 Flammability Rating 4:.....Highly Flammable