

# Dynatex®

## HS2500

Dynatex GTX HS2500 Trailer Sealant takes the place of most traditional adhesives and sealants and is designed to resist all on-the-road flexing and vibration. It is fast curing and provides **PERMANENT** elastic adhesion to most surfaces with both quick grab and excellent durability.



- Trailer Sealant/Adhesive
- Hi-Strength Multi-Seal
- Paintable
- Non-Streaking or Staining
- Seals Seams, Joints, Tears & Holes
- Bonds to most substrates
- Can be applied and tooled in most weather conditions
- No Shrinking
- Flexible
- VOC Compliant

**HIGH STRENGTH TRAILER SEALANT** meets ASTM C920, Type S, Grade NS, Class 35, Use T, NT, M, A, G & O; and Federal Specification TT-S-0230C, Type II, Class A.

### USE ON:

- Tractor Trailers
- RVs
- Buses
- Containers
- Many other adhesive & sealant applications.

### AVAILABLE IN:

- 49399 - White (12/case)
- 49398 - Grey (12/case)



\*\*NOT RECOMMENDED FOR USE AS A GLAZING SEALANT

# Dynatex®

## HS2500

### HIGH STRENGTH TRAILER SEALANT

#### TYPICAL PROPERTIES

##### UNCURED

Appearance .....	Smooth
Specific Gravity.....	1.6
Sag/Slump.....	Nil
Extrusion Rate .....	250 g/min.
Tack Free Time @ 75° F (24° C) and 50% R.H. ....	20 min.

##### CURED-PHYSICAL

Durometer, Shore A Hardness .....	48 pts.
Ultimate Tensile Strength .....	420 psi
Elongation.....	480%
Modulus .....	250 psi
Solid .....	98%

Service Temperature: 40° F to 200° F

Application Temperature: -95° F to 140° F

\*\*Primers may be required for certain substrates.

\*\*Information on this sheet is subject to change without notice, and should not be used for writing specifications. For additional information, contact Dynatex.



350 Ring Road  
Elizabethtown, KY 42701, USA  
270-769-5557 • 800-999-2937  
FAX: 270-769-6418  
www.dynatexinc.com