

Dynatex®

GTX-BRUSHABLE

Trailer Roof Sealant & Adhesive

- Flexible & Strong Sealant
- Resists Vibration
- Paintable
- Non-Streaking or Staining
- Seals Tears
- Fills Holes
- Waterproof
- Non-Streaking or Staining
- No Shrinking
- Flexible Seam Sealer
- VOC Compliant
- Non-Yellowing

USE ON:

- Tractor Trailers
- RVs
- Buses
- Containers
- Many other adhesive and sealant applications

Dynatex GTX-BRUSHABLE Trailer Roof Sealant takes the place of most traditional adhesives and sealants and is designed to resist all the on-the-road flexing and vibration. It cures quickly and provides permanent adhesion with excellent elasticity. It is specially formulated to offer outstanding primer-less adhesion to all basic substrates found in the transportation market, such as steel, aluminum, glass, vinyl, and wood. It can be applied and tooled in almost all weather conditions and can be painted within 30 minutes. It cures on exposure to atmospheric moisture to form a durable, flexible seal.

Part # 146204 Grey (4 1GAL TUB/case)



Dynatex®

GTX-BRUSHABLE

Trailer Roof Sealant & Adhesive

TYPICAL PROPERTIES

Appearance.....	Smooth
Color	Light Grey
Specific Gravity.....	1.53
Viscosity (cPs)	24,000
Skin Over Time (min)	4
Tack Free Time (Min)	35
Volatiles (%).....	2.73
Solids (%).....	97.27
Shore "D" ("A"*)	48*
Tensile Strength (psi)	173
Elongation (%)	320
Modulus (psi)	88

Primers may be required for certain substrates.

Information on this sheet is subject to change without notice, and should not be used for writing specifications. For additional information, contact Dynatex.