

DISC BRAKE QUIET PART NO. 143519

PHYSICAL PROPERTIES

Physical State	Aerosol
Color/Appearance	Red Liquid
Odor	Solvent odor
Specific Gravity	0.775
VOC %	59.5%
Vapor Pressure	N/A
Evaporation Rate	>1.00 (BuAc=1)
Solubility	Insoluble in water
Boiling/Cond. Point	133°F
pH	N/A
DOT Classification	Hazardous
Hazard Class	2.1



DESCRIPTION

Dynatex® Disc Brake Quiet forms a water resistant, high-temperature film that absorbs noise while quieting squeaks and squeals. Specially formulated to dampen the vibrations that cause brake noise. For use on the back of non-shimmed disc pads.

FEATURES

- Compatible with anti-lock brake systems
- Eliminates disc brake squeal
- Protects against corrosion
- Allows for easy disassembly
- For use on all cars and trucks
- Tested in accordance to 75/324/EEC Directive 6.1

TYPICAL APPLICATIONS

- Backing plates
- Brake pad contact points
- Disc brake pads
- Outboard and inboard pads for disc braking systems

DIRECTIONS

1. Remove the lug nuts holding the wheel assembly in place.
2. Remove the pins (or bolts) holding the caliper assembly to access the brake pad.
3. Remove dirt or grease from surface with *Dynatex® Brake & Parts Cleaner (P/N 49665)*.
4. Shake can thoroughly until the ball agitator inside the can is free. For best results, aerosol can should be at room temperature before spraying.
5. Holding can 8 to 10 inches from the back side of the disc pad press the nozzle and apply a light even coat. Note: Do not apply to the side which comes into contact with the rotor.
6. For consistent coverage, apply one to two additional coats.
7. Allow the product to dry a minimum of 10 minutes per coat, and then reassemble.

Packaging

Colors: Red

Size: 9 Oz Net Aerosol

STORAGE AND SHELF LIFE

Dynatex® Disc Brake Quiet should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. Store in accordance with NFPA 30B for level 3 aerosols. *Dynatex® Disc Brake Quiet* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® a division of **SOUDAL**

350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net

Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418

Website: www.dynatex.net