

ELECTRICAL PARTS CLEANER PART NO. 143548

PHYSICAL PROPERTIES

Physical State	Aerosol liquid
Color/Appearance.....	Clear, colorless
Odor	Ether-likier
Specific Gravity	1.6
Boiling/Cond. Point.....	250°F (121°C)
Solubility	0.015% @ 25°C
Evaporation Rate.....	0.09 (BuAc=1)
VOC %	Exempt
NFPA Flammability Rating	0
pH.....	6.8 – 8.4



DESCRIPTION

Dynatex® Electrical Parts Cleaner quickly dissolves and flushes away grease, oil and dirt while leaving no residue. Formulated for removing oil, grease, brake fluids, oxidized oils (gum) and asphalt from all types automotive parts and brakes. *Dynatex® Electrical Parts Cleaner* penetrates through dirt and corrosion and flushes them away, eliminating the need to disassemble. It leaves no residue, dries fast and is non-corrosive to metals. **Not safe for use on rubber or plastic parts.**

TYPICAL APPLICATIONS

- Air conditioning equipment
- Electrical motors
- Alternators
- Starting motors
- Cables
- Regulators
- Air compressors
- Battery chargers
- Portable tools, welders and more...

FEATURES

- Instantly cleans electrical parts
- Dries fast with no residue
- Eliminates dismantling
- Tested in accordance to 75/324/EEC Directive 6.1

DIRECTIONS FOR USE:

1. Provide adequate ventilation.
2. Protect painted surfaces from over-spray.
3. Shake can thoroughly before use.
Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
4. Holding can 8 to 10 inches from the surface for open area cleaning or using the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.

Packaging

Colors: Clear/ Colorless
Size: 16 Oz Net Aerosol

GENERAL INFORMATION

This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

STORAGE AND SHELF LIFE

Dynatex® Electrical Parts Cleaner should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. Store in accordance with NFPA 30B for level 1 aerosols.

Dynatex® Electrical Parts Cleaner has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® a division of **SOUDAL**

350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net

Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418

Website: www.dynatex.net