

CONTACT CLEANER PART NO. 143550

PHYSICAL PROPERTIES

Physical State	Liquid (Aerosol)
Color/Appearance.....	Water-white, clear
Odor	Hydrocarbon odor
Specific Gravity	0.7
Boiling/Cond. Point.....	>100°F
Solubility	Insoluble in water
Evaporation Rate.....	>1 (BuAc=1)
VOC %	96.0%
Vapor Pressure	Not Applicable
NFPA Flammability Rating	3*

***Highly Flammable**



DESCRIPTION

Dynatex® Contact Cleaner removes grease, dirt, oil and other surface contaminants from electrical and electronic devices. *Dynatex® Contact Cleaner* is fast drying, nonconductive, leaves no residue and is compatible with most plastics. Easily cleans oil, flux, dirt and other contaminants from contacts, switches and electric motors. This product is flammable and must therefore be used only on de-energized components and equipment. Always allow to dry completely and evacuate fumes before power is returned.

FEATURES

- Fast drying
- Leaves no residue
- Cleans easily
- Tested in accordance to 75/324/EEC Directive 6.1

TYPICAL APPLICATIONS

- Contacts
- Switches
- Electric Motors

DIRECTIONS FOR USE:

1. Turn off electrical equipment before cleaning.
2. Hold can 8 to 10 inches from surface to be cleaned.
3. Spray surfaces liberally.
4. Allow cleaned surface to dry completely.

ALWAYS TEST FOR COMPATIBILITY ON ALL PRODUCTS BEFORE USE

THIS PRODUCT SHOULD NOT BE USED FOR CLEANING CONDUITS

GENERAL INFORMATION

This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

Packaging

Colors: Clear

Size: 12 Oz Net Aerosol

STORAGE AND SHELF LIFE

Dynatex® Contact Cleaner should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse of storage building. Store in accordance with NFPA 30B for level 3 aerosols. *Dynatex® Contact Cleaner* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® a division of **SOUDAL**

350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net
Website: www.dynatex.net

Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418