

### GLASS CLEANER PART NO. 143555

#### PHYSICAL PROPERTIES

Physical State .....	Aerosol
Color/Appearance.....	Clear liquid
Odor .....	Mild
Specific Gravity .....	0.96
Boiling/Cond. Point.....	-44°F to 336°F
Flash Point.....	-156°F
Solubility .....	Complete
Evaporation Rate.....	Unknown
Vapor Density .....	Unknown
NFPA Flammability Rating .....	2



#### DESCRIPTION

*Dynatex® Glass Cleaner* is versatile and safe enough to use on your most delicate glass surfaces yet is strong enough to quickly cut through the toughest dirt, dust, and fingerprint and haze deposits. *Dynatex® Glass Cleaner* is biodegradable, ready to use, foaming, non-abrasive, professional grade, non-flammable and non-ozone depleting.

#### FEATURES

- VOC Compliant
- Contains no CFC's
- Foaming – Clings to vertical surfaces and minimizes run-off
- Non-Abrasive – Will not scratch or score equipment finish
- Non-Flammable – Aqueous formulation reduces risk of fire
- Professional Grade – Formulated for heavy duty, industrial applications
- Tested in accordance to 75/324/EEC Directive 6.1

#### TYPICAL APPLICATIONS

- Mirrors
- Chrome
- Stainless Steel
- Polished Metals
- Porcelain
- Removes bugs, road film, salt, grease, tar and paint over-spray

#### DIRECTIONS FOR USE:

1. Remove cap. Hold can upright 8 to 12 inches from surface to be cleaned.
2. Press valve button and spray sparingly.
3. Allow a few seconds for ingredients to penetrate.
4. Dry with paper towel or unsoiled cloth.

#### Packaging

Colors: Clear

Size: 19 Oz Net Aerosol

## GENERAL INFORMATION

**This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Material Safety Data Sheet.**

## STORAGE AND SHELF LIFE

*Dynatex® Glass Cleaner* should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. *Dynatex® Glass Cleaner* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

**Dynatex®** a division of **SOUDAL**

350 Ring Road  
Elizabethtown, KY 42701  
Email: sales@dynatex.net

Toll Free: (800) 999-2937  
Ph: (270) 769-5557  
Fax (270) 769-6418

Website: www.dynatex.net