

## TECHNICAL DATA SHEET

### BELT DRESSING PART NO. 143558

#### PHYSICAL PROPERTIES

Physical State .....	Aerosol
Color/Appearance.....	White foamy
Odor .....	Mild odor
Specific Gravity .....	0.95
Boiling/Cond. Point.....	Not established
Solubility .....	Soluble in water
Evaporation Rate.....	<1.00 (BuAc=1)
VOC % .....	15.23%
Vapor Pressure .....	Not applicable (Propellant)
NFPA Flammability Rating .....	1



#### DESCRIPTION

*Dynatex® Belt Dressing* extends belt life by conditioning against drying and cracking. Stops squeal and protects against belt slippage due to heat, cold, dampness, dust and glazing. *Dynatex® Belt Dressing* penetrates the cord fibers to restore pliability and flexibility. Recommended for use on all types of machinery and equipment with motor driven belts.

#### FEATURES

- Provides better grip and traction
- Stops belts from slipping and squealing
- Helps prevent premature wear, drying and cracking
- Easy application, aerosol spray for maximum coverage, extension tube for hard to reach areas
- Protects belts from deterioration due to oxidation and heat
- Tested in accordance to 75/324/EEC Directive 6.1

#### TYPICAL APPLICATIONS

- Industrial belt drives
- V-belts or flat belts of rubber, leather or fabric
- Automotive
- Farm equipment

**Note:** Not recommended for use on serpentine belts

#### DIRECTIONS FOR USE:

1. Provide adequate ventilation.
2. Shake can thoroughly before each use.
3. Belt should be clean and dry.
4. Stop engine before use.
5. Spray a thin coating on the pulley side of the belt.
6. Idle engine for a short period of time to run belt and evenly distribute coating.
7. Treatment may be repeated when belt squeals or slips.

**Note:** Prolonged or recurring squeaking is an indication that the belt should be replaced due to excessive wear and deterioration.

#### Packaging

Colors: Clear

Size: 12 Oz Net Aerosol

## GENERAL INFORMATION

**This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Material Safety Data Sheet.**

## STORAGE AND SHELF LIFE

*Dynatex® Belt Dressing* should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. Store in accordance with NFPA 30B for level 1 aerosols. *Dynatex® Belt Dressing* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

**Dynatex®** a division of **SOUDAL**

350 Ring Road  
Elizabethtown, KY 42701  
Email: sales@dynatex.net  
Website: www.dynatex.net

Toll Free: (800) 999-2937  
Ph: (270) 769-5557  
Fax (270) 769-6418