

## SCHOOL BUS YELLOW SEALANT/ ADHESIVE PART NO. 145990

### PHYSICAL PROPERTIES

|                              |                   |
|------------------------------|-------------------|
| Appearance.....              | Smooth Paste      |
| Color .....                  | School Bus Yellow |
| Specific Gravity .....       | 1.19              |
| Extrusion Rate (g/min) ..... | 285               |
| Slump (in) .....             | 0                 |
| Skin Over Time (min) .....   | 3                 |
| Tack Free Time (min).....    | 15                |
| Shore A Hardness .....       | 30                |
| Tensile Strength (psi).....  | 315               |
| Elongation (%) .....         | 700               |
| Modulus (psi).....           | 84                |
| VOC (g/L).....               | 32                |



### DESCRIPTION

**Dynatex® School Bus Yellow Sealant/ Adhesive** is a flexible, durable sealant, which bonds most materials, similar and dissimilar. Provides a water-tight silicone seal for a wide range of sealing and water-proofing applications. Eliminates leaks and drafts in windshield, and body side windows. Seals flashing and warning light signals. Can also be used as a body seam sealer. Fills voids and irregularities. Bonds and seals frayed wires, interior panels, fire-walls dashboards, seams joints and holes, signal lights and electrical connections. Secures wiring to prevent rattling. Temperature range -60°F to 450°F. provides permanent elastic seal and adhesion

### FEATURES

- Flexible and durable sealant
- Eliminates leaks
- Fills voids and irregularities
- Bonds and seals
- Secures wiring
- Water-tight
- VOC compliant

### TYPICAL APPLICATIONS

- Doors and windshields
- Escape hatches and window frames
- Body seams, patch joint, tears and holes
- Electrical connections and warning light signals
- Bond and seal frayed wires
- Body side windows

### Packaging

Colors: School Bus Yellow  
Size: 300ml Cartridge

---

## STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **Dynatex® School Bus Yellow Sealant/ Adhesive** has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

**Dynatex®** a division of **Soudal**

350 Ring Road  
Elizabethtown, KY 42701  
Email: [sales@dynatex.net](mailto:sales@dynatex.net)

Toll Free: (800) 999-2937  
Ph: (270) 769-5557  
Fax (270) 769-6418

Website: [www.dynatex.net](http://www.dynatex.net)