

**GTX BRUSHABLE TRAILER ROOF SEALANT
PART NO. 146204**

TYPICAL PROPERTIES

Uncured

Appearance.....	Smooth
Colors.....	Light Grey
Specific Gravity	1.53
Viscosity (cPs).....	24,000
Skin Over Time (min)	4
Tack Free Time (min)	35
Volatiles (%).....	2.73
Solids (%)	97.27
Durometer Shore A Hardness.....	48 points
Tensile Strength (psi)	173
Elongation (%).....	320
Modulus (psi).....	88



DESCRIPTION

Dynatex® GTX-BRUSHABLE Trailer Roof Sealant takes the place of most traditional adhesive and sealants and is designed to resist all the on-the-road flexing and vibration. It cures quickly and provides permanent adhesion with excellent elasticity. It is specially formulated to offer outstanding primer-less adhesion to all basic substrates found in the transportation market, such as steel, aluminum, glass, vinyl and wood. It can be applied and tooled in almost all weather conditions and can be painted within 30 minutes. It cures on exposure to atmospheric moisture to form a durable, flexible seal.

TYPICAL APPLICATIONS

Popular applications include:

- Tractor trailers
- RV's
- Buses
- Van conversions
- Shipping containers and many other adhesive /sealant applications
- Metal to metal

FEATURES

- Flexible and strong sealant
- Resists vibration
- Seals tears
- Fills holes
- Waterproof
- Paintable*
- Non-streaking or staining
- No shrinking
- Flexible seam sealer
- Non-yellowing
- VOC Compliant

**Always test small area for compatibility before applying.*

Packaging

Colors: Grey
Size: 1-Gallon Plastic Bucket

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **Dynatex® GTX-BRUSHABLE Trailer Roof Sealant** has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® a division of **SOUDAL**

350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net

Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418

Website: www.dynatex.net