# SOUDAL SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. SOUDAL reserves the Distributed by: Soudal Accumetric • Elizabethtown, KY 42701 • www.soudalusa.com • info@soudalusa.com • 877-873-8739

Remark: This information and all further technical advice are based on SOUDAL present knowledge and experience. However, SOUDAL assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, SOUDAL disclaims all WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

SWIPEX 100XXL WIPES

#### **Revision: 11/06/2015**

### **Technical Data:**

	Non woven wipes impregnated with a mixture of solvents, biodegradable non-ionic surfactants and skin emollients
Consistency	Non woven impregnated wipes
Density of liquid formula	Clear liquid
Density of liquid formula	

(\*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates. Test results are averages obtained under laboratory conditions. Reasonable variations can be expected.

**Product:** 

Heavy-duty non-woven wipes impregnated with a liquid formula for removing paint and other associated soils such as inks, adhesives, sealants, oils and grease from hands, tools and general hard surfaces.

#### Instructions:

Remove a wipe from the container and wiper over the surface to remove soiling. Soils will be absorbed into the cloth. Allow surface to air dry. Re-seal the container to retain moisture in remaining wipes.

#### **Applications:**

- Cleans and removes uncured sealant
- Cleans tools, surfaces, etc... from oil, ink, adhesives, grease, etc...
- Removes oil, sealant and adhesive stains, grease, etc... from hands

#### Packaging:

Plastic tub, containing 80 wipes

#### Shelf life:

12 months in unopened packaging in a cool and dry storage place at temperatures between +41°F and +77°Ē.

#### Surfaces:

Suitable for all non-porous surfaces. A preliminary compatibility test is necessary as some paints and powder coatings can be affected by Swipex. Do not use on porous surfaces such as untreated wood or natural stone.

right to make any changes according to technological progress or further developments

## Health and Safety Recommendation:

Keep out of reach of children. Avoid contact with the eyes and damaged skin. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice.

#### Remarks:

Test the compatibility of this product with all types of painted materials and powder coatings on a nonvisible spot.

#### Limited Warranty:

SOUDAL warrants product to be of good quality and will replace or, at our election, refund the purchase price of any products proved to be defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, SOUDAL MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and SOUDAL shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.



Technical Data Sheet



## Page 1 of 2